



BASE - 625 x 310 x 10

## CARACTERÍSTICAS TÉCNICAS / TECHNICAL DATA ISO 13006 - EN 14411

|              | CARACTERÍSTICAS TÉCNICAS<br>TECHNICAL CHARACTERISTICS                                                                                                                                                           | NORMATIVA<br>EN 14411<br>ISO 13006 | GRESMANC<br>SERIES<br>A1b |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|---------------------------|
| ISO 10545-2  | Características dimensionales<br>Dimensions and surface quality                                                                                                                                                 | Exigida<br>Required                | Garantizada<br>Guaranteed |
| ISO 10545-3  |  Absorción de agua<br>Water absorption                                                                                       | Grupo A1b $E < 0.5 < 3 \%$         | $E \leq 1.5 \%$           |
| ISO 10545-4  |  Resistencia a la flexión<br>Modulus of rupture                                                                              | Grupo A1b $\geq 23 \text{ N/mm}^2$ | $\geq 28 \text{ N/mm}^2$  |
| ISO 10545-7  |  Resistencia a la abrasión superficial de<br>baldosas esmaltadas (P.E.I.)<br>Resistance to superficial abrasion glazed tiles | —                                  | IV                        |
| ISO 10545-9  |  Resistencia al choque térmico<br>Thermal shock resistance                                                                   | Exigida<br>Required                | Garantizada<br>Guaranteed |
| ISO 10545-11 |  Resistencia al cuarteo:<br>Baldosas esmaltadas<br>Crack resistance: Glazed tiles                                            | Exigida<br>Required                | Garantizada<br>Guaranteed |
| ISO 10545-12 |  Resistencia a la helada<br>Frost resistance                                                                                 | Exigida<br>Required                | Garantizada<br>Guaranteed |
| ISO 10545-13 |  Resistencia química<br>Chemical resistance                                                                                  | Mínimo GB (glazed)                 | GA<br>GLA<br>GHA          |
| ISO 10545-14 |  Resistencia a las manchas<br>Stain resistance                                                                               | Mínimo clase 3                     | Garantizada<br>Guaranteed |

| SEGURIDAD / SAFETY | DESCRIPCIÓN<br>DESCRIPTION                                                                                                                                        | Coeficientes Antideslizamiento<br>Resultados<br>Non-slip coefficients Results |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| UNE ENV<br>12633   |  Resistencia al deslizamiento Rd (CTE)<br>Anti-slip resistance (Pendulum test) | CLASE 3<br>(Soft Tech C3: Easy cleaning<br>and soft touch)                    |